

Cable telefónico plano FTP 6 vías negro



Description

According German Post Office standard

1=white, 2=brown, 3=green, 4=yellow, 5=grey, 6=pink, 7=blue, 8=red, 9=black, 10=violet

Colour black, with drain wire

General data

Longitudinal water blocking	False
Radial water blocking	False
Outdoor use permitted	False
Circuit integrity	NoNono

Cable construction

Conductor category	K1.2 = single wire
Diameter conductor	0.33 mm
Core insulation	Polypropylene
Core identification	colour
Screen over stranding element	without
Screen over stranding	foil + braid
Armouring	False

Cable sheath

Protective sheath	sonstige
Material outer sheath	PVC
Halogen free (acc. EN 50267-2-2)	False
Flame retardant	NoNono
Low smoke (acc. EN 61034-2)	False

Environmental conditions

Operating temperature, flexible	60 – °C
Operating temperature, fix	60 – °C

Available variants

Article no.	Title	Outer diameter approx.	Colour outer sheath	Number of cores
92704.100	Modular Flat Cable 4-pole shielded, black, 100 m reel	2.5 x 5.2 mm	Black	4
92706.100	Modular Flat Cable 6-pole shielded, black, 100 m reel	2.5 x 7.0 mm	Black	6
92708.100	Modular Flat Cable 8-pole shielded, black, 100 m reel	9.3 mm	black	8

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.